


Find Me 1 Casambi integrated

New

09.3911.06 - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 169 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 4.0W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 20 |
| Beam angle C90-270 (°) | 20 |



Beam Angle: 20°

h(m) E(lx) D(m)

1 1124 0.35

2 281 0.70

3 125 1.06

4 70 1.41

5 45 1.76

Luminous flux luminaire
169 lm

Electrical

| | | | |
|-------------|---|------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | FLOS smart control, Electronic dimmable CASAMBI | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|----|
| Color | Chrome | Spot diameter (mm) | 33 |
| Orientation | Adjustable | Length (mm) | 33 |
| Weight (kg) | 0.11 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

