


Find Me 1 Casambi integrated

New

09.3911.06A - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 169 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 4.0W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 20 |
| Beam angle C90-270 (°) | 20 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 20° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 1124 | 0.35 | |
| 2 | 281 | 0.70 | |
| 3 | 125 | 1.06 | |
| 4 | 70 | 1.41 | |
| 5 | 45 | 1.76 | |

Luminous flux luminaire
169 lm

Electrical

| | | | |
|-------------|------------------|------------------|-----|
| Voltage (V) | 24 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable Casambi | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|----|
| Color | Chrome | Spot diameter (mm) | 33 |
| Orientation | Adjustable | Length (mm) | 33 |
| Weight (kg) | 0.11 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

