







## 9.3912.06A - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.


## Main specifications


Number of heads	1
Lamp category	LED
Power (W)	4.0W
System power (W)	4
CCT (K)	2700K

CRI 90 Net lumen (lm) 274 Mountings Track

Environment Indoor dry location







274 lm

**Emergency** 

Insulation class

3 410 0.72 4 231 0.95 148 1.19 Luminous flux luminaire

Without

14°

D(m)

0.24

0.48

Beam Angle:

h(m)

E(lx)

3691

923

1	
8	\/ <sub>\p^2</sub>



	- '	
Current (mA)	360	
Dimmable	Yes	
Driver	Remote	
	excluded	
Driver type	Dimmable	
• •	C 1:	

Electrical

Current (mA)	360	
Dimmable	Yes	
Driver	Remote	
	excluded	
Driver type	Dimmable	
	Casambi	

## Physical

Color	Chrome	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.11	Lifespan (L70 B10)	L80B50
Tilt (°) Rotation (°)	90 360	Ellespail (E70 B10)	LOODSO

24



Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

