





	V	IP 20 <b>IECEE</b>
<b>CE</b> <sup>GWT</sup> 850°		

## Find Me 1 Casambi integrated



## 09.3912.40A - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

Main specifications Number of heads Lamp category Power (W) System power (W) CCT (K)	1 LED 5.5W 5.5 2700K	CRI Net lumen (lm) Mountings Environment	90 309 Track Indoor dry	309	
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) UGRL Efficiency (lm/W)	Direct Power LED Symmetric Spot 14 14 4 56.18	90° 60° 30° 4168 cc Luminous flux 309 lm	¥	Beam Angle: 14°   h(m) E(lx) D(m)   1 4168 0.24   2 1042 0.48   3 463 0.72   4 261 0.95   5 167 1.19	
Electrical Voltage (V) Current (mA) Dimmable Driver Driver type	24 400 Yes Remote excluded Dimmable Casambi	Emergency Insulation class	Without III		
Physical Color Orientation Weight (kg) Tilt (°) Rotation (°)	White Adjustable 0.11 90 360	Spot diameter (mr Length (mm) Lifespan (L70 B10)	33		

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)