








■ 09.3912.CZA - Bronze

Main specifications

Number of heads	1	CRI
Lamp category	LED	Net lumen (lm)
Power (W)	5.5W	Mountings
System power (W)	5.5	Environment
CCT (K)	2700K	

Optical

Direct
Power LED
Symmetric
Spot
14
14
4
56.18



90 309

Track

Indoor dry location

Bea	ım Angle:	14°
h(m) E(lx)	D(m)
1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95
5	167	1.19

\wedge	
$\langle \langle \rangle$	
	\ //
8	/ _^ / [§]

₹ 03	(II)	F	I P 20	IECEE	EAC
CE	GWT 850°				

F	lectrical
_	- Cuicai

Voltage (V)	24	Emergency	Without
Current (mA)	400	Insulation class	III
Dimmable	Yes		
Driver	Remote		
	excluded		
Driver type	Dimmable		
	Casambi		

Physical

Color	Bronze	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.11	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)