









09.3913.06 - Chrome

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


Main specifications

Number of heads	1
_amp category	LED
Power (W)	4.0W
CCT (K)	2700K
CRI	90

Net lumen (lm) 164 Mountings Track Environment Indoor

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



1096 0.35 274 0.70 3 122 1.06 4 69 1.41 44 1.76

 $E(I_X)$

Beam Angle:

h(m)

20°

D(m)

Voltage (V) Dimmable	
Driver	
Driver type	

24.00

Emergency

Electrical

Dimmable	Yes
Priver	Remote
Priver type	FLOS smart
	control,
	Electronic
	dimmable
	CACAMADI

CASAMBI Without

Physical

Color	Chrome
Orientation	Adjustable
Weight (kg)	0.11
Rotation (°)	360
Spot diameter (mm)	33

Length (mm) 33

Insulation class

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

