


## Find Me 1 Casambi integrated

New

## 09.3913.06A - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	164
Power (W)	4.0W	Mountings	Track
System power (W)	4	Environment	Indoor dry location
CCT (K)	2700K		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	6
Efficiency (lm/W)	41



Beam Angle: 20°

h(m) E(lx) D(m)

1 1096 0.35

2 274 0.70

3 122 1.06

4 69 1.41

5 44 1.76

Luminous flux luminaire  
164 lm

## Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	360	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		

## Physical

Color	Chrome	Length (mm)	33
Orientation	Adjustable	Lifespan (L70 B10)	L80B50
Weight (kg)	0.11		
Rotation (°)	360		
Spot diameter (mm)	33		

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

