


## Find Me 1 Casambi integrated

New

09.3913.40A - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




### Main specifications

Number of heads	1	Net lumen (lm)	186
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle:	20°		
	h(m)	E(lx)	D(m)
1	1238	0.35	
2	310	0.70	
3	138	1.06	
4	77	1.41	
5	50	1.76	

Luminous flux luminaire  
186 lm

### Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

### Physical

Color	White	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.11		
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

