

## Find Me 1 Double Point

■ 09.3705.14C - Black

Recessed luminaire with two adjustable spots for indoor application. Remote power supply 500 mA not included.

Recessed luminaire with two adjustable spots for indoor application. Remote power supply 500 mA not included.




### Main specifications

<b>Number of heads</b>	2	<b>Net lumen (lm)</b>	365
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	14
<b>Beam angle C90-270 (°)</b>	14



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	4881	0.24
2	1220	0.49
3	542	0.73
4	305	0.97
5	195	1.21

Luminous flux luminaire  
365 lm (EXTREME CUT OFF)

### Electrical


<b>Voltage (V)</b>	12	<b>Insulation class</b>	III
<b>Dimmable</b>	No		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable, Dimmable, Casambi		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	153		
<b>Weight (kg)</b>	0.5		
<b>Tilt (°)</b>	70		

### Note

Accessories included (honeycomb and screening crosspiece).



## Find Me 1 Double Point



---

Continuous current power supply of  
6W, 100V / 14W, 240V – 50/60Hz with  
500 mA supply voltage  
60.8880

---

Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/750/800/900/1000/1050mA – 38W  
60.9207