

## Find Me 1 Mono Point (Trim/No Trim)

■ 09.3756.06 - Chrome

Recessed adjustable luminaire for indoor application. Remote power supply 500 mA not included.

Recessed adjustable luminaire for indoor application. Remote power supply 500 mA not included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	321
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	6W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	18
<b>Beam angle C90-270 (°)</b>	18



Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2784	0.31
2	696	0.62
3	309	0.93
4	174	1.23
5	111	1.54


Luminous flux luminaire  
321 lm



### Electrical

<b>Voltage (V)</b>	12	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Certification / Marking



### Physical

<b>Color</b>	Chrome	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable	<b>Spot diameter (mm)</b>	35
<b>Recessed depth (mm)</b>	137		
<b>Weight (kg)</b>	0.23		
<b>Tilt (°)</b>	70		

### Note

Accessories included (honeycomb and screening crosspiece). Remote power supply to be installed in an accessible place.

## Find Me 1 Mono Point (Trim/No Trim)



---

Constant Current Power Supply for  
LED. 15-20W  
60.8911

---

Continuous current power supply.  
Switch by trailing and leading edge  
dimming, mains dimming or push  
dimming. 32W  
60.8534

---

Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847



---

Constant Current Power Supply for  
LED. 1-10V switch or push dimming. 13-  
20W  
60.9188

---

Constant Current Power Supply for  
LED. 6W-100/14W-240V  
60.8880