





09.3820.40 - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

Main specifications

Number of heads	1	Net lumen (lm)	314
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Spot
Beam angle (°) 13
Beam angle C90-270 (°) 13



Luminous flux luminaire 314 lm

Insulation class

Beam Angle:		14°
h(m)) E(lx)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1 21

Electrical

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	Electronic,
	Electronic
	dimmable
	CASAMBI,
	Electronic
	dimmable 1-
	10V, Electronic
	dimmable DA

Emergency

Physical

Color	Whit
Orientation	Fixed
Weight (kg)	0.27
Spot diameter (mm)	33
Length (mm)	33

Note

Accessories included (honeycomb and screening crosspiece).

Without