



Find Me 1 Suspension

■ 09.3820.CZ - Bronze


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 314 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 5.5W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 13 |
| Beam angle C90-270 (°) | 13 |



Beam Angle: 14°

h(m) E(lx) D(m)

1 4193 0.24


2 1048 0.49

3 466 0.73

4 262 0.97

5 168 1.21

Luminous flux luminaire
314 lm



Electrical

| | | | |
|-------------|---|------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1- 10V, Electronic dimmable DALI | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|--------|
| Color | Bronze |
| Orientation | Fixed |
| Weight (kg) | 0.27 |
| Spot diameter (mm) | 33 |
| Length (mm) | 33 |

Note

Accessories included (honeycomb and screening crosspiece).

