



Find Me 1 Suspension

■ 09.3822.06A - Chrome


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

Main specifications

Number of heads	1	Net lumen (lm)	309
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	14




Beam Angle: 14°

h(m) E(lx) D(m)

1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95
5	167	1.19

Luminous flux luminaire
309 lm



Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable, Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	Chrome
Orientation	Fixed
Weight (kg)	0.27
Spot diameter (mm)	33
Length (mm)	33

Note

Accessories included (honeycomb and screening crosspiece).

