



# Find Me 1 Suspension

■ 09.3823.14 - Black


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

## Main specifications

| Number of heads | 1     | Net lumen (lm) | 186    |
|-----------------|-------|----------------|--------|
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 5.5W  | Environment    | Indoor |
| CCT (K)         | 2700K |                |        |
| CRI             | 90    |                |        |

## Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Medium
Beam angle (°) 20
Beam angle C90-270 (°) 20



Luminous flux luminaire 186 lm

Insulation class

| Beam Angle: |       | 20°  |
|-------------|-------|------|
| h(m)        | E(lx) | D(m) |
| 1           | 1238  | 0.35 |
| 2           | 310   | 0.70 |
| 3           | 138   | 1.06 |
| 4           | 77    | 1.41 |
| 5           | 50    | 1.76 |

#### Electrical

| Voltage (V) | 24.00           |  |
|-------------|-----------------|--|
| Dimmable    | Yes             |  |
| Driver      | Remote          |  |
| Driver type | Electronic,     |  |
|             | Electronic      |  |
|             | dimmable        |  |
|             | CASAMBI,        |  |
|             | Electronic      |  |
|             | dimmable 1-     |  |
|             | 10V, Electronic |  |
|             | dimmable DALI   |  |

Without

# Emergency Physical

| Color              | Black |
|--------------------|-------|
| Orientation        | Fixed |
| Weight (kg)        | 0.27  |
| Spot diameter (mm) | 33    |
| Length (mm)        | 33    |

## Note

Accessories included (honeycomb and screening crosspiece).