



## Find Me 1 Suspension

■ 09.3823.40A - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	186
Power (W)	5.5W	Mountings	Track
System power (W)	5.5	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	6
Efficiency (lm/W)	33.82



Beam Angle: 20°

h(m)	E(lx)	D(m)
1	1238	0.35
2	310	0.70
3	138	1.06
4	77	1.41
5	50	1.76

Luminous flux luminaire  
186 lm

### Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	400	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		

### Physical

Color	White	Lifespan (L70 B10)	L80B50
Orientation	Fixed		
Weight (kg)	0.27		
Spot diameter (mm)	33		
Length (mm)	33		

### Note

Accessories included (honeycomb and screening crosspiece).

