



Find Me 1 Suspension Casambi integrated

New

09.3920.18A - Deep Brown

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.


Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 314 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 5.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |




Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 14 |
| Beam angle C90-270 (°) | 14 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 14° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 4193 | 0.24 | |
| 2 | 1048 | 0.49 | |
| 3 | 466 | 0.73 | |
| 4 | 262 | 0.97 | |
| 5 | 168 | 1.21 | |

Luminous flux luminaire
314 lm



Electrical

| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable | | |
| Emergency | Casambi | | |
| | Without | | |

Physical

| | |
|--------------------|------------|
| Color | Deep Brown |
| Orientation | Fixed |
| Weight (kg) | 0.27 |
| Spot diameter (mm) | 33 |
| Length (mm) | 33 |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

