



## Find Me 1 Suspension Casambi integrated

New

09.3920.40A - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.

### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 314                 |
| Power (W)        | 5.5W  | Mountings      | Track               |
| System power (W) | 5.5   | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 14        |
| Beam angle C90-270 (°) | 14        |
| UGRL                   | 3         |
| Efficiency (lm/W)      | 57.09     |



Beam Angle: 14°

h(m) E(lx) D(m)

1 4193 0.24

2 1048 0.49

3 466 0.73

4 262 0.97

5 168 1.21

Luminous flux luminaire  
314 lm

### Electrical

|              |                                           |                  |         |
|--------------|-------------------------------------------|------------------|---------|
| Voltage (V)  | 24                                        | Emergency        | Without |
| Current (mA) | 400                                       | Insulation class | III     |
| Dimmable     | Yes                                       |                  |         |
| Driver       | Remote<br>excluded<br>Dimmable<br>Casambi |                  |         |
| Driver type  |                                           |                  |         |

### Physical

|                    |       |                    |        |
|--------------------|-------|--------------------|--------|
| Color              | White | Lifespan (L70 B10) | L80B50 |
| Orientation        | Fixed |                    |        |
| Weight (kg)        | 0.27  |                    |        |
| Spot diameter (mm) | 33    |                    |        |
| Length (mm)        | 33    |                    |        |

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

