



# Find Me 1 Suspension Casambi integrated



### 09.3920.CZ - Bronze


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.

N 4 ·	• • • • •	
Iviain	specifications	

•			
Number of heads	1	Net lumen (lm)	314
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

# Optical

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Direct Power LED Symmetric Spot 13 13



Bean	14°	
h(m)	E(lx)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1.21

314 lm

Electrical				
Voltage (V) Dimmable Driver Driver type Emergency	24.00 Yes Remote FLOS smart control, Electronic dimmable CASAMBI Without	Insulation class	III	
Physical				
Color Orientation Weight (kg) Spot diameter (mm) Length (mm)	Bronze Fixed 0.27 33 33			

# Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)