



GWT 850°











Find Me 1 Suspension Casambi integrated





09.3921.06A - Chrome

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ ${\it Casambi\ via\ Flos\ Control\ App\ to\ individually\ control\ the\ lights.\ Not\ suitable\ for\ vertical\ installations.}$

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	5.5W
CCT (K)	3000K
CRI	90

Net lumen (lm) 193 Mountings Track

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle: $E(I_X)$ D(m) h(m) 1285 0.35 321 0.70 3 143 1.06 4 80 1.41 51 1.76

20°

Luminous	flux	luminai
193 lm		

Electrical

Voltage (V)	24
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable
	Casambi
Emergency	Without

Insulation class

Physical

Color	Chrome
Orientation	Fixed
Weight (kg)	0.27
Spot diameter (mm)	33
Length (mm)	33

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)