

## Find Me 1 Suspension Casambi integrated

■ 09.3921.CZ - Bronze

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.

### Main specifications

Number of heads	1	Net lumen (lm)	193
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20



Beam Angle:	20°		
	h(m)	E(lx)	D(m)
1	1285	0.35	
2	321	0.70	
3	143	1.06	
4	80	1.41	
5	51	1.76	

Luminous flux luminaire  
193 lm

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	FLOS smart control, Electronic dimmable CASAMBI		
Emergency	Without		

### Physical

Color	Bronze
Orientation	Fixed
Weight (kg)	0.27
Spot diameter (mm)	33
Length (mm)	33

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time).

### Certification / Marking

