















09.3921.CZA - Bronze

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	5.5W
System power (W)	5.5
CCT (K)	3000K

CRI 90 Net lumen (lm) 193 Mountings Track

Environment Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	20
Beam angle C90-270 (°)	20
UGRL	6
Efficiency (lm/W)	35.09



Without

L80B50

Beam Angle: 20° $E(I_X)$ D(m) h(m) 1285 0.35 321 0.70 3 143 1.06 4 80 1.41 51 1.76

Luminous nux iu	mimair
193 lm	

Emergency

Insulation class

Electrical

Voltage (V)	24
Current (mA)	400
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable
	Casambi

Physical

Color	Bronze	Lifespan (L70 B10)
Orientation	Fixed	
Weight (kg)	0.27	
Spot diameter (mm)	33	
Length (mm)	33	

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)