




# Find Me 1 Suspension Casambi integrated





 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights. Not suitable for vertical installations.


## Main specifications

| Number of heads | 1     |
|-----------------|-------|
| amp category    | LED   |
| Power (W)       | 5.5W  |
| CCT (K)         | 2700K |
| CRI             | 90    |
|                 |       |

Net lumen (lm) 309 Mountings Track Environment Indoor

## Optical

| ΞD  |
|-----|
| ric |
|     |
|     |
|     |
|     |



Insulation class

14° Beam Angle: h(m) = E(Ix)D(m) 4168 0.24 1042 0.48 3 463 0.72 4 261 0.95 167 1.19

| Voltage (V) | 24.00      |
|-------------|------------|
| Dimmable    | Yes        |
| Driver      | Remote     |
| Driver type | FLOS smart |
|             | control,   |
|             | Electronic |
|             | dimmable   |

CASAMBI Without

**Emergency** 


#### Physical

Electrical

| Color              | Black |
|--------------------|-------|
| Orientation        | Fixed |
| Weight (kg)        | 0.27  |
| Spot diameter (mm) | 33    |
| Length (mm)        | 33    |
|                    |       |

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



ø33

