

Find Me 1 Suspension Casambi integrated

09.3922.40 - White

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included. Not suitable for vertical installations.

Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 309 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 5.5W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 13 |
| Beam angle C90-270 (°) | 13 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 14° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 4168 | 0.24 | |
| 2 | 1042 | 0.48 | |
| 3 | 463 | 0.72 | |
| 4 | 261 | 0.95 | |
| 5 | 167 | 1.19 | |

Luminous flux luminaire
309 lm

Electrical

| | | | |
|-------------|---|------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | FLOS smart control, Electronic dimmable CASAMBI | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------|
| Color | White |
| Orientation | Fixed |
| Weight (kg) | 0.27 |
| Spot diameter (mm) | 33 |
| Length (mm) | 33 |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time).

Certification / Marking

