

## Find Me 2

New



## 09.3860.40 - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

## Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 531    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 10.5W | Environment    | Indoor |
| CCT (K)         | 3000K |                |        |
| CRI             | 90    |                |        |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 10        |
| Beam angle C90-270 (°) | 10        |



Beam Angle: 10°

h(m) E(lx) D(m)

1 10249 0.18

2 2562 0.35

3 1139 0.53

4 641 0.70

5 410 0.88

Luminous flux luminaire  
531 lm

## Electrical

|             |                                                                                                                    |                  |     |
|-------------|--------------------------------------------------------------------------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                                                                                              | Insulation class | III |
| Dimmable    | Yes                                                                                                                |                  |     |
| Driver      | Remote                                                                                                             |                  |     |
| Driver type | Electronic,<br>Electronic<br>dimmable<br>CASAMBI,<br>Electronic<br>dimmable 1-<br>10V, Electronic<br>dimmable DALI |                  |     |
| Emergency   | Without                                                                                                            |                  |     |

## Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | White      | Spot diameter (mm) | 46 |
| Orientation  | Adjustable | Length (mm)        | 46 |
| Weight (kg)  | 0,06       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

## Note

Accessories included (honeycomb and screening crosspiece).

