



GWT 850°













Find Me 2





09.3862.CZA - Bronze

 ${\sf LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Main specifications


Number of heads Lamp category LED Power (W) 10.5W CCT (K) 2700K CRI 90

479 Net lumen (lm) Mountings Track

Environment Indoor dry location

Optical

Lighting type LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



Luminous flux luminaire 479 lm

Beam Angle:		10°
h(m)	E(lx)	D(m)
1	9244	0.18
2	2311	0.35
3	1027	0.53
4	578	0.70
5	370	0.88

Electrical

Insulation class Voltage (V) 24 Ш Dimmable Yes Driver Remote excluded Driver type

Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1

Without **Emergency**

Physical

Color Spot diameter (mm) 46 Bronze Orientation Adjustable Length (mm) Weight (kg) 0.06 Tilt (°) 90 Rotation (°) 360

Note

Accessories included (honeycomb and screening crosspiece).