















# Find Me 2



### 09.3862.CZA - Bronze

 ${\sf LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.


## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	479
Power (W)	10.5W	Mountings	Track

System power (W) 10.5 **Environment** Indoor dry location 2700K CCT (K)

## Optical

Lighting type LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10 **UGRL** Efficiency (lm/W) 45.62



Luminous flux luminaire 479 lm

Without

Ш

Beam Angle:		10
h(m)	E(l×)	D(m
1	9244	0.18
2	2311	0.35
3	1027	0.53
4	578	0.70
5	370	0.88

## Electrical

Voltage (V)	24	Emergency
Current (mA)	760	Insulation class
Dimmable	Yes	
Driver	Remote	
	excluded	
Driver type	Non Dimmable,	
	Dimmable	
	Casamhi	

Dimmable 1-10V, Dimmable DALI 1

Phys	ical
гнуэ	ıcaı

Rotation (°)

Color	Bronze	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		

#### Note

Accessories included (honeycomb and screening crosspiece).

360