


## Find Me 2

New

### 09.3863.06A - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	379
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	19
<b>Beam angle C90-270 (°)</b>	19



<b>Beam Angle:</b>	19°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	1709	0.34	
2	427	0.67	
3	190	1.01	
4	107	1.34	
5	68	1.68	

Luminous flux luminaire  
379 lm

### Electrical

<b>Voltage (V)</b>	24	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Chrome	<b>Spot diameter (mm)</b>	46
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	46
<b>Weight (kg)</b>	0.06		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece).

