



## Find Me 2

New

09.3865.06A - Chrome

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 312                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track               |
| <b>Power (W)</b>       | 8W    | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 2700K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Flood     |
| <b>Beam angle (°)</b>         | 32        |
| <b>Beam angle C90-270 (°)</b> | 32        |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 32°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 620          | 0.57        |  |
| 2                  | 155          | 1.15        |  |
| 3                  | 69           | 1.72        |  |
| 4                  | 39           | 2.29        |  |
| 5                  | 25           | 2.87        |  |

Luminous flux luminaire  
312 lm

### Electrical

|                    |   |                         |     |
|--------------------|---|-------------------------|-----|
| <b>Voltage (V)</b> | 24  | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | Yes   |                         |     |
| <b>Driver</b>      | Remote excluded   |                         |     |
| <b>Driver type</b> | Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1 |                         |     |
| <b>Emergency</b>   | Without   |                         |     |

### Physical

|                     |            |                           |    |
|---------------------|------------|---------------------------|----|
| <b>Color</b>        | Chrome     | <b>Spot diameter (mm)</b> | 46 |
| <b>Orientation</b>  | Adjustable | <b>Length (mm)</b>        | 46 |
| <b>Weight (kg)</b>  | 0.06       |                           |    |
| <b>Tilt (°)</b>     | 90         |                           |    |
| <b>Rotation (°)</b> | 360        |                           |    |

### Note

Accessories included (honeycomb and screening crosspiece).