

## Find Me 2

New

### 09.3865.14A - Black


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1-10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	364
Power (W)	10.5W	Mountings	Track
System power (W)	10.5	Environment	Indoor dry location
CCT (K)	2700K		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32
UGRL	6
Efficiency (lm/W)	34.67



Luminous flux luminaire  
364 lm

Beam Angle: 32°

h(m)	E(lx)	D(m)
1	722	0.57
2	180	1.15
3	80	1.72
4	45	2.29
5	29	2.87

## Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	760	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		

## Physical

Color	Black	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

## Note

Accessories included (honeycomb and screening crosspiece).