



81

99

139

Find Me 2 Casambi integrated





09.3960.CZ - Bronze

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.

Main specifications

Number of heads	1
amp category	LED
Power (W)	10.5W
CCT (K)	3000K
CRI	90

Direct

10 10

Power LED


Symmetric Spot

Net lumen (lm) 531 Mountings Track Environment Indoor

Optical

Electrical

Lighting type
LED type
Light distribution
Optical type
Beam angle (°)
Beam angle C90-270 (°)



h(m) = E(Ix)D(m) 10249 0.18 2562 0.35 3 1139 0.53 4 641 0.70 410 0.88

Beam Angle:

10°

531 lm	Luminous fil
	531 lm





19

120



ø46

Voltage (V) Dimmable Driver Driver type	24.00 Yes Remote FLOS smart control, Electronic dimmable CASAMBI	Insulation class	III
Emergency	Without		
Physical			
Color	Bronze	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0,06		
Tilt (°)	90		
()			

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)