





09.3961.06 - Chrome

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	W8
CCT (K)	3000K
CRI	90

Net lumen (lm) 489 Mountings Track Environment

Indoor

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	19
Beam angle C90-270 (°)	19



Beam Angle: 19° h(m) = E(Ix)D(m) 1869 0.34 467 0.67 3 208 1.01 4 117 1.34 75 1.68

414 lm

Insulation class

6			
120		99	139
1			ı
	ø46		

	\F7	I P
(AL)	V	20

Electrical

voitage (v)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmable

dimmable CASAMBI

Without

Emergency Physical

Color	Chrome	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0,06		
Tilt (°)	90		
Rotation (°)	360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)