



## Find Me 2 Casambi integrated

New

### 09.3961.06A - Chrome


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	414
Power (W)	8W	Mountings	Track
System power (W)	8	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	19°
Beam angle C90-270 (°)	19°
UGRL	8
Efficiency (lm/W)	51.75



Beam Angle: 19°

h(m) E(lx) D(m)

1 1869 0.34

2 467 0.67

3 208 1.01

4 117 1.34

5 75 1.68

Luminous flux luminaire  
414 lm

### Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	570	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded Dimmable Casambi		

### Physical

Color	Chrome	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

