



## Find Me 2 Casambi integrated

New

## ■ 09.3963.14A - Black

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	441
Power (W)	10.5W	Mountings	Track
System power (W)	10.5	Environment	Indoor dry location
CCT (K)	2700K		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	19°
Beam angle C90-270 (°)	19°
UGRL	8
Efficiency (lm/W)	42



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	1991	0.34
2	498	0.67
3	221	1.01
4	124	1.34
5	80	1.68

Luminous flux luminaire  
441 lm

## Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	765	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		

## Physical

Color	Black	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)