


09.3963.40 - White

## Main specifications

Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	10.5W	Environment
CCT (K)	2700K	
CDI	90	

## Optical

Direct
Power LED
Symmetric
Medium
19
19



441 Track

Indoor

Bean	Beam Angle:	
h(m)	E(lx)	D(m
1	1991	0.34
2	498	0.67
3	221	1.01
4	124	1.34
5	80	1.68

	81	, <del>,,,,,</del>	r	
19				
120		99	139	
	ø46			

$\bigcirc$	\F7	<b>I</b> P
ふひ	V	20

Electrical			
Voltage (V)	24.00	Insulation class	Ш
Dimmable	Yes		
Driver	Remote		
Driver type	FLOS smart		
	control		

control, Electronic dimmable CASAMBI Without

Physical Physical

rnysicai			
Color	White	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0,06		
Tilt (°)	90		
Rotation (°)	360		

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)