


## Find Me 2 Casambi integrated

■ 09.3963.CZ - Bronze

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included.

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 1–10-V DALI or Casambi driver in broadcast mode. Dimmer not included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	441
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	9.9W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	19
<b>Beam angle C90-270 (°)</b>	19



Beam Angle:	19°		
	h(m)	E(lx)	D(m)
1	1991	0.34	
2	498	0.67	
3	221	1.01	
4	124	1.34	
5	80	1.68	

Luminous flux luminaire  
441 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	FLOS smart control, Electronic dimmable CASAMBI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Bronze	<b>Spot diameter (mm)</b>	46
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	46
<b>Weight (kg)</b>	0,06		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time).

### Certification / Marking

