









#### 09.3965.06 - Chrome


### Main specifications

Number of heads	1
_amp category	LED
Power (W)	8W
CCT (K)	2700K
CRI	90

Net lumen (lm) 364 Mountings Track Environment Indoor

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32
Beam angle (°)	32



 h(m)
 E(lx)
 D(m)

 1
 620
 0.57

 2
 155
 1.15

 3
 69
 1.72

 4
 39
 2.29

 5
 25
 2.87

Beam Angle:

32°

Luminous	t
312 lm	

Insulation class

# 120 19

ø46



E	ec	tri	ca

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmable

Electronic dimmable CASAMBI Without

## Emergency Physical

Color	Chrome	Spot diameter (mm)	46
Orientation	Adjustable	Length (mm)	46
Weight (kg)	0,06		
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)