







9.3965.14 - Black

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.


Main specifications

| Number of heads | 1 |
|-----------------|-------|
| _amp category | LED |
| Power (W) | 10.5W |
| CCT (K) | 2700K |
| CRI | 90 |
| | |

Net lumen (lm) 364 Mountings Track Environment Indoor

Optical

| Lighting type | Direct |
|------------------------|-----------|
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 32 |
| Beam angle C90-270 (°) | 32 |
| | |



Insulation class

 $E(I_X)$ D(m) h(m) 1 722 0.57 180 1.15 3 80 1.72 4 45 2.29 29 2.87

Beam Angle:

32°

| Luminous no |
|-------------|
| 364 lm |
| |

Electrical

| voitage (v) | 24.00 |
|-------------|------------|
| Dimmable | Yes |
| Driver | Remote |
| Driver type | FLOS smart |
| | control, |
| | Electronic |
| | dimmahla |

Electronic dimmable CASAMBI Without

Emergency

Physical

| Color | Black | Spot diameter (mm) | 46 |
|--------------|------------|--------------------|----|
| Orientation | Adjustable | Length (mm) | 46 |
| Weight (kg) | 0,06 | _ | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



