





09.3965.CZ - Bronze


Main specifications

Number of heads	1
amp category	LED
Power (W)	10.5W
CCT (K)	2700K
CRI	90

Net lumen (lm) 364
Mountings Track
Environment Indoor

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	32
Beam angle C90-270 (°)	32



Insulation class

Beam Angle:		32°
h(m)	E(l x)	D(m)
1	722	0.57
2	180	1.15
3	80	1.72
4	45	2.29
5	29	2.87

Luminous flux luminair
364 lm

Electrical

voitage (v)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmahla

Electronic dimmable CASAMBI Without

Emergency

Physical

Color	Bronze	Spot diameter (mm) 46
Orientation	Adjustable	Length (mm) 46
Weight (kg)	0,06	
Tilt (°)	90	
Rotation (°)	360	

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



