



## Fort Knox Ceiling


■ 09.2156.05A - Polished Aluminium

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


## Main specifications

Number of heads	1	Net lumen (lm)	860
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		



## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27



Beam Angle: 27°

$h(m)$	$E(I_x)$	$D(m)$
1	2140	0.48
2	535	0.97
3	238	1.45
4	134	1.94
5	86	2.42


Luminous flux lumineuse  
860 lm

## Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	
Emergency	Without	

## Physical

Color	Polished
Orientation	Aluminium
Weight (kg)	Adjustable
Tilt (°)	0.70
Rotation (°)	95
	355



Fort Knox Ceiling



NEODIMIUM  
08.8501.ND



AMBER FILTER  
08.8501.66.OD



SKY BLUE FILTER  
08.8501.65.OD



BLUE FILTER  
08.8501.64.OD



Honeycomb  
08.8502.14



DAYLIGHT  
08.8501.DL



COLD LIGHT  
08.8501.CL



HOT LIGHT  
08.8501.69



RED FILTER  
08.8501.67.OD