



## Fort Knox Ceiling

■ 09.2165.14A - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1096
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	13.8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		



### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	19
<b>Beam angle C90-270 (°)</b>	19



Beam Angle: 19°

h(m) E(lx) D(m)

1 3779 0.33


2 945 0.66

3 420 0.98

4 236 1.31

5 151 1.64

Luminous flux luminaire  
1096 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.70
<b>Tilt (°)</b>	95
<b>Rotation (°)</b>	355



## Fort Knox Ceiling



---

SKY BLUE FILTER  
08.8501.65.OD



---

DAYLIGHT  
08.8501.DL



---

RED FILTER  
08.8501.67.OD



---

BLUE FILTER  
08.8501.64.OD



---

Honeycomb  
08.8502.14



---

AMBER FILTER  
08.8501.66.OD



---

COLD LIGHT  
08.8501.CL



---

NEODIMIUM  
08.8501.ND



---

HOT LIGHT  
08.8501.69