





■ 09.2167.14A - Black

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included. Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Optical

Number of neads	I	ivet iumen (in
Lamp category	LED	Mountings
Power (W)	13.8W	Environment
CCT (K)	3000K	
CRI	80	

Net lumen (lm) ntings

1089 Ceiling surface Indoor dry location





0		
42	40	

151	43	68
1		120



Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	61
Beam angle C90-270 (°)	61

90°
60° 60°
30° 130° cd 30°
Luminous flux luminaire

30-		130	io c	a t	30-
Lum	ino	us f	lux	lumi	naire
1089	lm				

Bean	Beam Angle:	
h(m)	E(lx)	D(m)
1	1305	1.17
2	326	2.34
3	145	3.51
4	82	4.68
5	52	5.85

Frequency (Hz)	
Dimmable	
Driver	
Driver type	

Yes Integrated Dimmer on board **Emergency** Without

50/60

Insulation class

Physical

Electrical

Black
Adjustable
0.70
95
355

Fort Knox Ceiling







COLD LIGHT 08.8501.CL

AMBER FILTER 08.8501.66.OD

DAYLIGHT 08.8501.DL







HOT LIGHT 08.8501.69

BLUE FILTER 08.8501.64.OD

RED FILTER 08.8501.67.OD







NEODIMIUM 08.8501.ND

SKY BLUE FILTER 08.8501.65.OD

Honeycomb 08.8502.14