



## Fort Knox Track

09.2150.05A - Polished Aluminium


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

Number of heads	1	Net lumen (lm)	834
Lamp category	LED	Mountings	Track
Power (W)	9.2W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	17



Beam Angle: 17°

h(m)	E(lx)	D(m)
1	3247	0.30
2	812	0.59
3	361	0.89
4	203	1.19
5	130	1.49

Luminous flux luminaire  
834 lm




### Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

### Physical

Color	Polished Aluminium
Orientation	Adjustable
Weight (kg)	0.60
Tilt (°)	95
Rotation (°)	355



# Fort Knox Track



---

Recessed box for fix-point  
60.3022.11



---

Recessed box for fix-point  
60.3022.14



---

Fix-point  
60.3023.11



---

Fix-point  
60.3023.14



---

Fix-point  
60.3023.29



---

BLUE FILTER  
08.8501.64.OD



---

SKY BLUE FILTER  
08.8501.65.OD



---

AMBER FILTER  
08.8501.66.OD



---

RED FILTER  
08.8501.67.OD



---

**HOT LIGHT**  
08.8501.69



---

**COLD LIGHT**  
08.8501.CL



---

**DAYLIGHT**  
08.8501.DL



---

**NEODIMIUM**  
08.8501.ND



---

**Honeycomb**  
08.8502.14