



Fort Knox Track

■ 09.2150.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	834
Lamp category	LED	Mountings	Track
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	17
Beam angle C90-270 (°)	17



Beam Angle: 17°

h(m)	E(lx)	D(m)
1	3247	0.30
2	812	0.59
3	361	0.89
4	203	1.19
5	130	1.49

Luminous flux luminaire
834 lm



Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.60
Tilt (°)	95
Rotation (°)	355



Fort Knox Track



Recessed box for fix-point
60.3022.11



Recessed box for fix-point
60.3022.14



Fix-point
60.3023.11



NEODIMIUM
08.8501.ND



SKY BLUE FILTER
08.8501.65.OD



AMBER FILTER
08.8501.66.OD



Fix-point
60.3023.14



Fix-point
60.3023.29



HOT LIGHT
08.8501.69



DAYLIGHT
08.8501.DL



RED FILTER
08.8501.67.OD



Honeycomb
08.8502.14



COLD LIGHT
08.8501.CL



BLUE FILTER
08.8501.64.OD