



Fort Knox Track

09.2151.05A - Polished Aluminium


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	860
Lamp category	LED	Mountings	Track
Power (W)	9.2W	Environment	Indoor
CCT (K)	3000K		
CRI	80		


Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27



Beam Angle: 27°		
h(m)	E(lx)	D(m)
1	2140	0.48
2	535	0.97
3	238	1.45
4	134	1.94
5	86	2.42

Luminous flux luminaire
860 lm




Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Polished Aluminium
Orientation	Adjustable
Weight (kg)	0.60
Tilt (°)	95
Rotation (°)	355



Fort Knox Track



Recessed box for fix-point
60.3022.11



Recessed box for fix-point
60.3022.14



Fix-point
60.3023.11



Fix-point
60.3023.14



Fix-point
60.3023.29



BLUE FILTER
08.8501.64.OD



SKY BLUE FILTER
08.8501.65.OD



AMBER FILTER
08.8501.66.OD



RED FILTER
08.8501.67.OD



HOT LIGHT
08.8501.69



COLD LIGHT
08.8501.CL



DAYLIGHT
08.8501.DL



NEODIMIUM
08.8501.ND



Honeycomb
08.8502.14