



## Fort Knox Track

■ 09.2151.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	860
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	27
<b>Beam angle C90-270 (°)</b>	27



<b>Beam Angle:</b>	27°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2140	0.48	
2	535	0.97	
3	238	1.45	
4	134	1.94	
5	86	2.42	

Luminous flux luminaire  
860 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.60
<b>Tilt (°)</b>	95
<b>Rotation (°)</b>	355



## Fort Knox Track



---

HOT LIGHT  
08.8501.69



---

RED FILTER  
08.8501.67.OD



---

Recessed box for fix-point  
60.3022.11



---

COLD LIGHT  
08.8501.CL



---

AMBER FILTER  
08.8501.66.OD



---

Honeycomb  
08.8502.14



---

NEODIMIUM  
08.8501.ND



---

BLUE FILTER  
08.8501.64.OD



---

DAYLIGHT  
08.8501.DL



---

SKY BLUE FILTER  
08.8501.65.OD



---

Fix-point  
60.3023.29



---

Fix-point  
60.3023.14



---

Fix-point  
60.3023.11



---

Recessed box for fix-point  
60.3022.14