



## Fort Knox Track

### ■ 09.2152.14A - Black


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

#### Main specifications

Number of heads	1	Net lumen (lm)	831
Lamp category	LED	Mountings	Track
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

#### Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	57
Beam angle C90-270 (°)	57



Beam Angle: 57°

h(m)	E(lx)	D(m)
1	1062	1.08
2	266	2.16
3	118	3.24
4	66	4.32
5	42	5.40

Luminous flux luminaire  
831 lm



#### Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

#### Physical

Color	Black
Orientation	Adjustable
Weight (kg)	0.60
Tilt (°)	95
Rotation (°)	355



Fort Knox Track



NEODIMIUM  
08.8501.ND



Recessed box for fix-point  
60.3022.14



BLUE FILTER  
08.8501.64.OD



DAYLIGHT  
08.8501.DL



RED FILTER  
08.8501.67.OD



Fix-point  
60.3023.11



AMBER FILTER  
08.8501.66.OD



Fix-point  
60.3023.14



Honeycomb  
08.8502.14



---

Fix-point  
60.3023.29



---

SKY BLUE FILTER  
08.8501.65.OD



---

COLD LIGHT  
08.8501.CL



---

HOT LIGHT  
08.8501.69



---

Recessed box for fix-point  
60.3022.11