



## Fort Knox Track

09.2161.05A - Polished Aluminium


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1125
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	13.8W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	27
<b>Beam angle C90-270 (°)</b>	27



Beam Angle: 27°

h(m)	E(lx)	D(m)
1	2753	0.48
2	688	0.95
3	306	1.43
4	172	1.91
5	110	2.38

Luminous flux luminaire  
1125 lm




### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmer on board		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Polished Aluminium
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.60
<b>Tilt (°)</b>	95
<b>Rotation (°)</b>	355



## Fort Knox Track



---

Recessed box for fix-point  
60.3022.11



---

Recessed box for fix-point  
60.3022.14



---

Fix-point  
60.3023.11



---

Fix-point  
60.3023.14



---

Fix-point  
60.3023.29



---

BLUE FILTER  
08.8501.64.OD



---

SKY BLUE FILTER  
08.8501.65.OD



---

AMBER FILTER  
08.8501.66.OD



---

RED FILTER  
08.8501.67.OD



---

**HOT LIGHT**  
08.8501.69



---

**COLD LIGHT**  
08.8501.CL



---

**DAYLIGHT**  
08.8501.DL



---

**NEODIMIUM**  
08.8501.ND



---

**Honeycomb**  
08.8502.14