



Fort Knox Track

■ 09.2161.30A - White


Spotlight to be installed on 3-phase track with LED light source. 220-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	1125
Lamp category	LED	Mountings	Track
Power (W)	13.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27



Beam Angle: 27°

h(m)	E(lx)	D(m)
1	2753	0.48
2	688	0.95
3	306	1.43
4	172	1.91
5	110	2.38

Luminous flux luminaire
1125 lm




Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmer on board		
Emergency	Without		

Physical

Color	White
Orientation	Adjustable
Weight (kg)	0.60
Tilt (°)	95
Rotation (°)	355



Fort Knox Track



Fix-point
60.3023.14



Fix-point
60.3023.29



SKY BLUE FILTER
08.8501.65.OD



AMBER FILTER
08.8501.66.OD



Honeycomb
08.8502.14



BLUE FILTER
08.8501.64.OD



DAYLIGHT
08.8501.DL



Recessed box for fix-point
60.3022.11



NEODIMIUM
08.8501.ND



COLD LIGHT
08.8501.CL



HOT LIGHT
08.8501.69



Recessed box for fix-point
60.3022.14



RED FILTER
08.8501.67.OD



Fix-point
60.3023.11