

## Fort Knox Wall LED Dali Version

09.2112.05ADA - Polished Aluminium

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2676
<b>Lamp category</b>	LED	<b>Mountings</b>	Wall surface
<b>Power (W)</b>	32W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Indirect
<b>LED type</b>	Power LED
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall Washer Up
<b>Beam angle (°)</b>	39
<b>Beam angle C90-270 (°)</b>	62



<b>Beam Angle: 39°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	778	3.39
2	194	6.77
3	86	10.16
4	49	13.55
5	31	16.94

Luminous flux luminaire  
2676 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	Polished Aluminium
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.40

