



G-O Amber Light

09.3201.30A - White


Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Main specifications

Lamp category	LED	Mountings	Wall recessed
Power (W)	1.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	2		

Optical



Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	72
Beam angle C90-270 (°)	72



Beam Angle: 72°

h(m)	E(lx)	D(m)
1	1	1.46
2	0	2.92
3	0	4.38
4	0	5.85
5	0	7.31

Luminous flux luminaire
2 lm



Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	56
Weight (kg)	0.11

Note


Equipment for remote installation in an accesible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.



G-O Amber Light



Dimmable DALI control unit with 1 channel for 24V LED modules. Power supply not included
60.8635



Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60H
60.9157



Prepared for recessing
08.8422.00



Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W
60.8703